

PRODUCT DESCRIPTION

BEX® Advanced Performance CJ-4 Synthetic Blend Diesel Engine Oils are specially formulated with EX³ to provide extra engine protection in 3 key areas: viscosity stability, extended wear performance, and resistance to engine buildup. Utilizing advanced technology, BEX® oils exceed current industry performance requirements. Always consult the vehicle manual for proper fluid & maintenance guidelines. BEX® oils are warranted against defect when used & stored properly.

FEATURES & BENEFITS

- Outperforms conventional diesel engine oils
- Advanced protection against sludge & soot for peak engine performance
- Superior additive technology retains viscosity & reduces engine wear
- Helps increase horsepower and fuel economy

TYPICAL PROPERTIES

TEST NAME	ASTM Method	10W-30	10W-40	15W-40
Kinematic Viscosity @ 100° C, cSt	D445	12	12	14.5
Kinematic Viscosity @ 40° C, cSt	D445	82.8	84.5	114.5
Viscosity Index	D2270	140	140	150
Flash Point °C / °F	D92	226 / 438	226 / 438	225 / 437
Pour Point °C / °F	D97	-40 / -40	-40 / -40	-40 / -40
TBN mgKOH/g	D2896	10	10.1	10
NOACK Volatility, %	D5800	12	11.5	12
Color	D1500	2.0	2.0	2.0

Typical test data are average values only. Minor variations, which do not affect performance, may occur.

PACKAGING DETAIL & PART NUMBERS

PRODUCT PACK SIZE	UNIT WEIGHT	Cubic Feet	PALLET QTY	PALLET WEIGHT	PART NO.	PART NO.	PART NO.
Case 12/ 1L, net 12L	25.2	0.78	112	2862	B116Q	B117Q	B115Q
Case 4/ 4L, net 16L	33.5	1.03	72	2452	B116L	B117L	B115L
Case 4/ 5L, net 20L	42.5	1.22	72	3100	B116G	B117G	B115G
Pail 18.9L (5 gal)	38.0	1.24	70	2700	B116P	B117P	B115P
Pail 20L	40.2	1.24	70	2854	B116J	B117J	B115J
Drum 208L (55 gal)	428	10.52	4	1752	B116D	B117D	B115D
Tote 1000L (265 gal)	1931	49.4	1	1931	B116T	B117T	B115T

TYPICAL APPLICATIONS

- 5W-30 meets the performance requirement of API CK-4, ACEA E6, MB 228.51, Caterpillar ECF-3, Mack EOS 4.5, Cummins CES 20086, Detroit Diesel DFS 93K222, Renault VI RLD-4
- 5W-40 meets the performance requirements of API CK-4, ACEA E9, Allison C-4, MAN 3275/3575, DD DFS 93K222, MB 228.3/.31, Mack EO-0/EOS-4.5, MTU 2.1, Global DHD-1, Ford WSS-M2C171-E, Renault RLD-4, Volvo VDS-4

HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable