

PRODUCT DESCRIPTION

BEX® ATF-III is formulated with high viscosity-index paraffinic base stocks and premium performance additives. It's a premium grade multi-functional transmission lubricant. Contains a premium performance additive package designed for excellent oxidation stability and thermal resistance as well as excellent friction modification properties. Also suitable for use in power steering units where the manufacturer recommends a Dexron III or Mercon fluid for its systems. Always consult the vehicle or equipment manual for proper fluid & maintenance guidelines. BEX® products are warranted against defect when used & stored properly.

FEATURES & BENEFITS

- Provides excellent friction modification properties
- Optimal thermal resistance & oxidation stability
- Protects critical system parts from rust & corrosion

TYPICAL PROPERTIES

TEST NAME	ASTM Method	Results	Results
Kinematic Viscosity @ 100° C, cSt	D445	7.2	7.2
Kinematic Viscosity @ 40° C, cSt	D445	35.9	35.9
Viscosity Index	D2270	170	170
Flash Point °C / °F	D92	195 / 383	195 / 383
Pour Point °C / °F	D97	-47 / -52	-47 / -52
Foaming Test	D892	< 50/0	< 50/0
Appearance		Red	Amber

Typical test data may vary. Minor variations, which do not affect performance, may occur.

PACKAGING DETAIL & PART NUMBERS

PRODUCT PACK SIZE	UNIT WEIGHT	Cubic Feet	PALLET QTY	PALLET WEIGHT	PART NO.	PART NO.
Case 12/ 1L, net 12L	25.2	0.78	98	2515	B400Q	B411Q
Case 4/ 4L, net 16L	33.5	1.03	60	2055	B400L	B411L
Case 4/ 5L, net 20L	42.5	1.22	50	2170	B400G	B411G
Pail 18.9L (5 gal)	38.0	1.24	42	1640	B400P	B411P
Pail 20L	40.2	1.24	42	1735	B400J	B411J
Drum 208L (55 gal)	428	10.52	4	1760	B400D	B411D
Tote 1000L (265 gal)	1930	49.4	1	1930	B400T	B411T

TYPICAL APPLICATIONS

- Most domestic passenger cars, light trucks, SUVs & vans manufactured before 2006
- Suitable for use in GM DEXRON®, DEXRON® II, II-E, III, III-G, III-H, Ford MERCON®, M2C-33, M2C-138-CJ, and M2C-166-H or Type A, Detroit Diesel Allison C-3, C-4 Caterpillar TO-2
- Mobile hydraulic & industrial systems and other rotary air compressors under specified service requirements

HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.