

PRODUCT DESCRIPTION

BEX® Full Synthetic DEX-VI is formulated from premium synthetic base stocks and a state-of-the-art additive system to meet or exceed the performance requirements for fluids listed herein. Consult the owner manual for proper fluid requirements and service recommendations. All BEX® products are warranted against defect when stored & used properly.

FEATURES & BENEFITS

- Superior shear stability & protection against wear, varnish and sludge formation
- Exceptional frictional properties for smooth shifting
- Superior thermal stability & maximum resistance to thermal breakdown
- Delivers optimum resistance to fluid oxidation in severe operating conditions
- Includes active anti-wear agents to protect critical transmission components
- Compatible with conventional fluids whether used in a complete fluid exchange or top-off
- Meets low-viscosity OEM transmission fluid requirements

TYPICAL PROPERTIES

TEST NAME	ASTM Method	SYN MV ATF RED
Kinematic Viscosity @ 100° C, cSt	D445	6.0
Kinematic Viscosity @ 40° C, cSt	D445	29.65
Viscosity Index	D2270	155
Flash Point °C / °F	D92	210 / 410
Pour Point °C / °F	D97	-50 / -58
Brookfield Viscosity, Cp @ 40° C	D2983	12,000

Typical test data may vary. Minor variations, which do not affect performance, may occur

PACKAGING DETAIL & PART NUMBERS

PRODUCT PACK SIZE	UNIT WEIGHT	CUBIC FEET	PALLET QTY	PALLET WEIGHT	PART NO.
Case 12/ 1L, net 12L	25.2	0.78	98	2515	B401Q
Case 4/ 4L, net 16L	33.5	1.03	60	2055	B401L
Case 4/ 5L, net 20L	42.5	1.22	50	2170	B401G
Pail 18.9L (5 gal)	38.0	1.24	42	1640	B401P
Pail 20L	40.2	1.24	42	1735	B401J
Drum 208L (55 gal)	428	10.52	4	1760	B401D
Tote 1000L (265 gal)	1930	49.4	1	1930	B401T

TYPICAL APPLICATIONS

- Where GM and Ford DEXRON® VI or MERCON® LV fluids are recommended
- Suitable for use where applicable in vehicles: Allison, Audi, BMW, CAT, Chrysler, Daewoo, Daihatsu, Fiat, Honda, Hyundai, Isuzu, Jaguar, JWS, Lexus, Man, Mazda, MB, Mini Cooper, Mitsubishi, Mopar, Nissan, Opel, Peugeot, Porsche, SAAB, Saturn, Scion, Subaru, Suzuki, Toyota, Voith, Volvo, VW, ZF

HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.