## **PRODUCT DESCRIPTION**

ULTIMATE PERFORMANCE

BEX<sup>®</sup> Premium DOT 3 Brake Fluid is specially compounded with ethylene glycol to meet or exceed the highest safety standards and performance requirement. Our formula complies with Federal Motor Vehicle Safety Standard 116 and SAE J1703 and ISO 4925. It can be certified by ABIC Testing Laboratories, Inc. if required by specific import customs agencies. Always consult the vehicle or equipment manual for proper fluid & maintenance guidelines. BEX<sup>®</sup> products are warranted against defect when used & stored properly.

## **FEATURES & BENEFITS**

- Minimum Wet Boiling Point of 140° C (284° F)
- Optimal protection and performance
- Protects critical system parts to extend vehicle life
- Balanced performance and durability during operating conditions
- Can be mixed with other approved DOT 3 brake fluids

## **TYPICAL PROPERTIES**

| TEST NAME                                    | DOT 3     |  |
|--|-----------|--|
| Kinematic Viscosity @ 100° C, cSt            | 2.12      |  |
| Kinematic Viscosity @ 40° C, cSt             | 1188      |  |
| Equilibrium Reflex Boiling Point °C / °F     | 255 / 491 |  |
| Wet Equilibrium Reflex Boiling Point °C / °F | 140 / 284 |  |
| Corrosion, FMVSS 116                         | Pass      |  |
| Rubber Swell, FMVSS 116                      | Pass      |  |
| Specific Gravity @ 60° F                     | 1.02      |  |
| Evaporation/Weight Loss                      | 47%       |  |
| Color  | amber     |  |

Typical test data are average values only. Minor variations, which do not affect performance, may occur.

# **PACKAGING DETAIL & PART NUMBERS**

| PRODUCT PACK SIZE       | UNIT   | Cubic | PALLET | PALLET | PART  |
|-------------------------|--------|-------|--------|--------|-------|
|                         | WEIGHT | Feet  | QTY    | WEIGH  | NO.   |
|                         |        |       |        | Т      |       |
| Case 12/ 354 mL (12 oz) | 12.5   | 0.40  | 130    | 1670   | B405C |
| Drum 208L (55 gl)       | 420    | 10.52 | 4      | 1752   | B405D |
| Tote 1000L (265 gl)     | 1920   | 49.4  | 1      | 1931   | B405T |

# **TYPICAL APPLICATIONS**

- Most domestic & foreign passenger cars, light trucks SUVs & vans
- For use in all disc and drum brake systems, including ABS, that require a DOT 3 fluid

HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

Made in the USA

