

PRODUCT DESCRIPTION

BEX® Synthetic High Performance Motorcycle Oils are specially formulated with synthetic base stocks and premium performance additives. Synthetic BEX oils with EX³ provide extra engine protection in three key areas: thermal stability, clutch protection, and clutch performance. Utilizing advanced synthetic technology, BEX® oils meet or exceed current industry performance requirements. Always consult the equipment owner manual for proper fluid & maintenance guidelines. BEX® oils are warranted against defect when used & stored properly.

FEATURES & BENEFITS

- Synthetic technology resists viscosity breakdown & delivers consistent & steady operation
- Protects during rapid RPM increase under extreme conditions
- Sophisticated dispersant technology provides exceptional cleanliness & prevents formation of sludge
- Delivers superior wet-clutch performance & protection
- Optimal power transfer and smooth shifting during both racing & normal conditions

TYPICAL PROPERTIES

TEST NAME	ASTM Method	5W-30	5W-40	10W-60	15W-40	15W-50	20W-50
Kinematic Viscosity @ 100° C, cSt	D445	11.0	14.5	23	14.5	18.0	18.0
Kinematic Viscosity @ 40° C, cSt	D445	64.25	89.2	158.4	103.4	122.05	148.95
Viscosity Index	D2270	165	170	175	145	165	135
Flash Point °C / °F	D92	215 / 419	210 / 410	215 / 419	220 / 428	220 / 428	225 / 437
Pour Point °C / °F	D97	-43 / -45	-42 / -43	-40 / -40	-35 / -31	-33 / -27	-30 / -22
Specific Gravity @ 60°F	D4052	0.87	0.87	0.87	0.87	0.87	0.88
NOACK Volatility, %	D5800	13	13	12.5	10	10	8
Color	D1500	2.5	2.5	2.5	2.5	2.5	2.5

Typical test data may vary. Minor variations, which do not affect performance, may occur.

PACKAGING DETAIL & PART NUMBERS

PRODUCT PACK SIZE	UNIT WEIGHT	Cubic Feet	PALLET QTY	PALLET WEIGHT	PART NO.	PART NO.	PART NO.	PART NO.	PART NO.	PART NO.
Case 12/ 1L, net 12L	25.2	0.78	98	2515	B201Q	B202Q	B203Q	B204Q	B205Q	B200Q
Case 4/ 4L, net 16L	33.5	1.03	60	2055	B201L	B202L	B203L	B204L	B205L	B200L
Case 4/ 5L, net 20L	42.5	1.22	50	2170	B201G	B202G	B203G	B204G	B205G	B200G
Pail 18.9L (5 gl)	38.0	1.24	42	1640	B201P	B202P	B203P	B204P	B205P	B200P
Pail 20L	40.2	1.24	42	1735	B201J	B202J	B203J	B204J	B205J	B200J
Drum 208L (55 gl)	428	10.52	4	1760	B201D	B202D	B203D	B204D	B205D	B200D
Tote 1000L (265 gl)	1930	49.4	1	1930	B201T	B202T	B203T	B204T	B205T	B200T

TYPICAL APPLICATIONS

- Any application requiring a four-stroke (4T) oil meeting the requirements of JASO MA-2 or API SM
- Recommended for use in high performance motorcycles, high RPM race-tuned 4T motorcycle engines with integral gear boxes and wet clutches
- Suitable for all season use, including snowmobiles, ATVs

HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.