



## PRODUCT DESCRIPTION

BEX® Heavy Duty Performance CH-4 and CF-4 Diesel Engine Oils are specially formulated to provide extra protection in older diesel engines. Also formulated for thermal endurance and viscosity stability. Utilizing pure virgin US base oils plus advanced additive technology, BEX® oils exceed current industry performance requirements. Always consult the vehicle or equipment manual for proper fluid & maintenance guidelines. BEX® oils are warranted against defect when used & stored properly.

## FEATURES & BENEFITS

- Cleaning power for extended engine performance
- Protection against sludge, soot & varnish build up
- Special additives retain viscosity & reduce wear on older engines
- Helps increase horsepower and fuel economy
- Delivers good dispersant, detergent, anti-wear, anti-corrosion, anti-oxidant & anti-foaming properties

## TYPICAL PROPERTIES

TEST NAME	ASTM Method	10W-40	15W-40	15W-50	20W-50	25W-60
Kinematic Viscosity @ 100° C, cSt	D445	14.5	14.5	17.3	18.3	24.0
Kinematic Viscosity @ 40° C, cSt	D445	94.4	103.4	119.4	158.1	252.15
Viscosity Index	D2270	160	145	160	130	120
Flash Point °C / °F	D92	210 / 410	220 / 428	220 / 428	225 / 437	235 / 455
Pour Point °C / °F	D97	-40 / -40	-33 / -27	-33 / -27	-30 / -22	-20 / 4
TBN mgKOH/g	D2896	8	8	8	8	9
NOACK Volatility, %	D5800	13	10	10	8	9
Color	D1500	3	3	3	3	Green

*Typical test data may vary. Minor variations, which do not affect performance, may occur.*

## PACKAGING DETAIL & PART NUMBERS

PRODUCT PACK SIZE	UNIT WEIGHT	Cubic Feet	PALLET QTY	PALLET WEIGHT	PART NO.				
Case 12/ 1L, net 12L	25.2	0.78	98	2515	B903Q	B901Q	B904Q	B902Q	B906Q
Case 4/ 4L, net 16L	33.5	1.03	60	2055	B903L	B901L	B904L	B902L	B906L
Case 4/ 5L, net 20L	42.5	1.22	50	2170	B903G	B901G	B904G	B902G	B906G
Pail 18.9L (5 gl)	38.0	1.24	42	1640	B903P	B901P	B904P	B902P	B906P
Drum 208L (55 gl)	428	10.52	4	1760	B903D	B901D	B904D	B902D	B906D
Tote 1000L (265 gl)	1930	49.4	1	1930	B903T	B901T	B904T	B902T	B906T

## TYPICAL APPLICATIONS

- Meets the performance requirement of API CH-4, CF-4, CF-2, CF and SL, SJ, SG, SF
- Recommended for use in light and heavy duty trucks
- Suitable for use in various applications in the construction and agriculture industries

*HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.*

Made in the USA



Rev. 02/2026