

PRODUCT DESCRIPTION

BEX® Advanced Performance CJ-4 Synthetic Blend Diesel Engine Oils are specially formulated with EX³ to provide extra engine protection in 3 key areas: viscosity stability, extended wear performance, and resistance to engine buildup. These oils are parasyntetic crankcase lubricants for use in modern engines. Utilizing advanced additive technology, BEX® oils exceed current industry performance requirements. Always consult the vehicle manual for proper fluid & maintenance guidelines. BEX® oils are warranted against defect when used & stored properly.

FEATURES & BENEFITS

- Outperforms conventional diesel engine oils
- Especially effective at sustaining emission control system durability using particulate filters
- Offers enhanced protection against oxidation, viscosity loss due to shear, and oil aeration
- Delivers protection against catalyst poisoning, particulate filter blocking, engine wear, & piston deposits
- Also protects against degradation of low & high temperature properties & soot related viscosity increase

TYPICAL PROPERTIES

TEST NAME	ASTM Method	15W-40	15W-50	20W-50
Kinematic Viscosity @ 100° C, cSt	D445	14.5	17.5	18.5
Kinematic Viscosity @ 40° C, cSt	D445	103.4	129.25	160.55
Viscosity Index	D2270	145	150	130
Flash Point °C / °F	D92	220 / 428	220 / 428	225 / 437
Pour Point °C / °F	D97	-35 / -31	-35 / -31	-30 / -22
TBN mgKOH/g	D2896	9	9	9
Color	D1500	Amber	Transparent	Liquid

Typical test data may vary. Minor variations, which do not affect performance, may occur.

PACKAGING DETAIL & PART NUMBERS

PRODUCT PACK SIZE	UNIT WEIGHT	CUBIC FEET	PALLET QUANTITY	PALLET WEIGHT	PART NO.	PART NO.	PART NO.
Case 12/ 1L, net 12L	25.2	0.78	96	2515	B118Q	B119Q	B150Q
Case 4/ 4L, net 16L	33.5	1.03	60	2055	B118L	B119L	B150L
Case 4/ 5L, net 20L	42.5	1.22	40	1750	B118G	B119G	B150G
Pail 18.9L (5 gal)	38.0	1.24	42	1640	B118P	B119P	B150P
Drum 208L (55 gal)	428	10.52	4	1760	B118D	B119D	B150D
Tote 1000L (265 gal)	1930	49.4	1	1930	B118T	B119T	B150T

TYPICAL APPLICATIONS

- Exceeds the performance requirement of API CJ-4, CI-4 PLUS , CI-4, CH-4,CF-4, CH-4, CF-4, CF-2, CF and API SN, SM, SL, SJ, SG
- Designed for use in high-speed 4 stroke diesel engines to meet 2017 on-highway and Tier 4 off road emission standards, as well as previous model year diesel engines

HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.