



PRODUCT DESCRIPTION

BEX® Full Synthetic CVT Fluid is formulated from premium synthetic base stocks and a state-of-the-art additive system to meet or exceed the performance requirements of applications listed below. Can be used in most Continuously Variable Transmissions, chain or belt. Consult the owner manual for proper fluid requirements and service recommendations. All BEX® products are warranted against defect when stored & used properly.

FEATURES & BENEFITS

- Outstanding power to fight varnish and sludge formation
- Exceptional frictional properties for smooth shifting & durability
- Delivers optimum resistance to fluid oxidation in severe operating conditions
- Includes active anti-wear agents to protect critical transmission components
- Superior variator torque capacity that can prevent belt or chain slippage
- Excellent low temperature properties

TYPICAL PROPERTIES

TEST NAME	ASTM Method	SYN MV ATF LO-VIS (RED)
Kinematic Viscosity @ 100° C, cSt	D445	7.2
Kinematic Viscosity @ 40° C, cSt	D445	34.3
Viscosity Index	D2270	180
Flash Point °C / °F	D92	210 / 410
Pour Point °C / °F	D97	-50 / -58

Typical test data may vary. Minor variations, which do not affect performance, may occur

PACKAGING DETAIL & PART NUMBERS

PRODUCT PACK SIZE	UNIT WEIGHT	CUBIC FEET	PALLET QTY	PALLET WEIGHT	PART NO.
Case 12/ 1L, net 12L	25.2	0.78	98	2515	B403Q
Case 4/ 4L, net 16L	33.5	1.03	60	2055	B403L
Case 4/ 5L, net 20L	42.5	1.22	50	2170	B403G
Pail 18.9L (5 gl)	38.0	1.24	42	1640	B403P
Pail 20L	40.2	1.24	42	1735	B403J
Drum 208L (55 gl)	428	10.52	4	1760	B403D
Tote 1000L (265 gl)	1930	49.4	1	1930	B403T

TYPICAL APPLICATIONS

AUDI TL 52180; G052 180 A2; G052 516	MERCEDES BENZ CVT28 / MB 236.20
BMW 83 22 0 136 376; 83 22 0 429 154 (EZL 799A)	MINI COOPER EZL799 / ZF CVT V1
DAIHATSU AMMIX DC and DFE, FLUID TC	MAZDA CVT F 3320; TC; NS-2; CVTF Green 1; CVTF Green 2
CHRYSLER/DODGE/JEEP NS-2, CVT+4, MOPAR CVT+4	NISSAN CVT FLUID NS-1, NS-2, NS-3
FORD CFT23, 30, MERCON C	PUNCH EZL 799A
FUJIYUKO i-CVTF FG	SHELL GREEN IV
GM/SATURN DEX-CVT	SUBARU j-CVT; Lineartronic CVTF; j-CVTF FG; K0425Y0710, CV-30, e-CVT
HONDA MULTI MATIC FLUID (HMMF) HCF-2	TOYOTA CVT FLUID TC and FE
HYUNDAI / KIA SP-CVT-1	VOLVO CVT 4959
LEXUS FLUID TC, FE	VW TL 52180, G 052 180 A2; G 052 516
MAZDA CVTF 3320	

HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

Made in the USA



Rev. 02/2020