



## PRODUCT DESCRIPTION

BEX® Full Synthetic ATF-MB is formulated from premium synthetic base stocks and a state-of-the-art additive system to meet or exceed the performance requirement for MB 236.17. Fluid color is a golden yellow. Consult the owner manual for proper fluid requirements and service recommendations. All BEX® products are warranted against defect when stored & used properly.

## FEATURES & BENEFITS

- Superior shear stability & protection against wear, varnish and sludge formation
- Exceptional frictional properties for smooth shifting
- Superior thermal stability & maximum resistance to thermal breakdown
- Delivers optimum resistance to fluid oxidation in severe operating conditions
- Includes active anti-wear agents to protect critical transmission components
- Compatible with conventional fluids whether used in a complete fluid exchange or top-off
- Meets low-viscosity OEM transmission fluid requirements

## TYPICAL APPLICATIONS

- Meets the performance requirements for Mercedes Benz 236.17

## TYPICAL PROPERTIES

TEST NAME	ASTM Method	SYN ATF-MBR
Kinematic Viscosity @ 100° C, cSt	D445	6.0
Kinematic Viscosity @ 40° C, cSt	D445	29.65
Viscosity Index	D2270	155
Flash Point °C / °F	D92	210 / 410
Pour Point °C / °F	D97	-50 / -58
Brookfield Viscosity, Cp @ 40° C	D2983	12,000

*Typical test data may vary. Minor variations, which do not affect performance, may occur*

## PACKAGING DETAIL & PART NUMBERS

PRODUCT PACK SIZE	UNIT WEIGHT	CUBIC FEET	PALLET QTY	PALLET WEIGHT	PART NO.	PART NO.
Case 12/ 1L, net 12L	25.2	0.78	98	2515	B402Q	B415Q
Case 4/ 4L, net 16L	33.5	1.03	60	2055	B402L	B415L
Case 4/ 5L, net 20L	42.5	1.22	50	2170	B402G	B415G
Pail 18.9L (5 gal)	38.0	1.24	42	1640	B402P	B415P
Pail 20L	40.2	1.24	42	1735	B402J	B415J
Drum 208L (55 gal)	428	10.52	4	1760	B402D	B415D
Tote 1000L (265 gal)	1930	49.4	1	1930	B402T	B415T

*Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.*

*HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.*

Made in the USA



Rev. 06/18/21