



PRODUCT DESCRIPTION

BEX® Full Synthetic Ultra Low Viscosity ATF-ULV is formulated from premium synthetic base stocks and a state-of-the-art premium additive system, specially engineered and recommended for use with ultra low viscosity requirements. Always consult the vehicle owner manual for proper fluid requirements and recommendations. All BEX® products are warranted against defect when stored & used properly.

FEATURES & BENEFITS

- Optimized balance of friction modifiers
- Provides outstanding anti-shudder properties
- Delivers superior shudder durability
- Formulated specifically for use in extended drain applications
- Delivers excellent resistance to fluid oxidation in severe operating conditions
- Formulated with fully synthetics base stocks for maximum resistance to thermal breakdown
- Includes active anti-wear agents to protect critical transmission components

TYPICAL PROPERTIES

TEST NAME	ASTM METHOD	TYPICAL RESULT
Viscosity, cSt @ 40°C, cSt	D445	19.2
Viscosity, cSt @ 100°C, cSt	D445	4.5
Viscosity Index	D2270	152
Brookfield Viscosity @ -40°C, cP	D2983	4,500
Pour Point, °C	D97	-51 / -59.8
Flash Point	D92	190 / 374
Appearance / Color		red

Typical test data may vary. Minor variations, which do not affect performance, may occur.

PACKAGING DETAIL & PART NUMBERS

PRODUCT PACK SIZE	UNIT WEIGHT	Cubic Feet	PALLET QTY	PALLET WEIGHT	PART NO.
Case 12/ 1L, net 12L	25.2	0.78	96	2355	B417Q
Case 4/ 4L, net 16L	33.5	1.03	60	2055	B417L
Case 4/ 5L, net 20L	42.5	1.22	50	2170	B417G
Pail 18.9L (5 gal)	38.0	1.24	56	2170	B417P
Pail 20L	40.2	1.24	56	2290	B417J
Drum 208L (55 gal)	428	10.52	4	1760	B417D
Tote 1000L (265 gal)	1930	49.4	1	1930	B417T

TYPICAL APPLICATIONS

- Recommended for use in Mercon ULV applications
- Recommend for use when ultra-low-viscosity ATF is required
- Suitable for use in ATF 9 applications
- This fluid is NOT recommended for use in CVT, DCT, Ford Type F & Type G

HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

Made in the USA



Rev. 11/2025