



## PRODUCT DESCRIPTION

BEX® Premium Performance Gasoline Engine Oils Conventional SN are specially formulated to provide superior protection and effectively keep critical engine parts clean. Utilizing the best virgin base oil and premium additive technology, BEX® oils exceed current industry performance requirements. Always consult the vehicle manual for proper fluid & maintenance guidelines. BEX® oils are warranted against defect when used & stored properly.

## FEATURES & BENEFITS

- Helps keep engines clean for peak engine performance
- Superior protection against sludge & soot build up
- Friction modifiers reduce engine wear
- Enhances fuel economy

## TYPICAL PROPERTIES

TEST NAME	ASTM Method	5W-20	5W-30	10W-30	10W-40	20W-50
Kinematic Viscosity @ 100° C, cSt	D445	8.0	10.8	11.0	14.5	18.3
Kinematic Viscosity @ 40° C, cSt	D445	45.4	62.8	59.55	91.75	158.1
Viscosity Index	D2270	150	165	150	165	130
Flash Point °C / °F	D92	205 / 401	210 / 410	215 / 419	210 / 410	220 / 428
Pour Point °C / °F	D97	-42 / -43	-42 / -43	-40 / -40	-40 / -40	-30 / -22
Specific Gravity @ 60°F	D4052	0.86	0.86	0.87	0.86	0.87
NOACK Volatility, %	D5800	13	13	11	13	8
Color	D1500	2.5	2.5	2.5	2.5	2.5

*Typical test data may vary. Minor variations, which do not affect performance, may occur.*

## PACKAGING DETAIL & PART NUMBERS

PRODUCT PACK SIZE	UNIT WEIGHT	Cubic Feet	PALLET QTY	PALLET WEIGHT	PART NO.	PART NO.	PART NO.	PART NO.	PART NO.
Case 12/ 1L, net 12L	25.2	0.78	98	2515	B120Q	B121Q	B122Q	B123Q	B124Q
Case 4/ 4L, net 16L	33.5	1.03	60	2055	B120L	B121L	B122L	B123L	B124L
Case 4/ 5L, net 20L	42.5	1.22	60	2170	B120G	B121G	B122G	B123G	B124G
Pail 18.9L (5 gl)	38.0	1.24	42	1640	B120P	B121P	B122P	B123P	B124P
Pail 20L	40.2	1.24	42	1735	B120J	B121J	B122J	B123J	B124J
Drum 208L (55 gl)	428	10.52	4	1760	B120D	B121D	B122D	B123D	B124D
Tote 1000L (265 gl)	1930	49.4	1	1930	B120T	B121T	B122T	B123T	B124T

## TYPICAL APPLICATIONS

- SAE 5W-20, 5W-30, 10W-30 meet requirements of SN PLUS, ILSAC GF-5, Chrysler MS-6395, GM-6094M
- SAE 10W-40, 20W-50 meet the performance requirements of API SN PLUS
- 20W-50 has a higher viscosity reserve to fully protect engines under higher operating speeds, temperatures, and other adverse conditions

*HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.*

Made in the USA



Rev. 02/2020