

## PRODUCT DESCRIPTION

BEX® Ultimate Performance Synthetic Oils are specially formulated with EX<sup>3</sup> to provide extra engine protection in 3 key areas: viscosity stability, extended wear performance, and resistance to engine buildup. Utilizing advanced synthetic technology, BEX® oils exceed current industry performance requirements. Always consult the vehicle manual for proper fluid & maintenance guidelines. BEX® oils are warranted against defect when used & stored properly.

## FEATURES & BENEFITS

- 100% synthetic technology to extend drain intervals
- Ultimate protection against sludge & soot for peak engine performance
- Friction modifiers reduce engine wear
- Helps maximize fuel economy

## TYPICAL PROPERTIES

TEST NAME	ASTM Method	0W-40	5W-40	5W-50	10W-40
Kinematic Viscosity @ 100° C, cSt	D445	13.0	14.5	18.5	14.5
Kinematic Viscosity @ 40° C, cSt	D445	73.65	86.8	115	89.2
Viscosity Index	D2270	180	175	180	170
Flash Point °C / °F	D92	210 / 410	215 / 419	215 / 419	210 / 410
Pour Point °C / °F	D97	-47 / -52	-42 / -43	-42 / -43	-40 / -40
Specific Gravity @ 60°F	D4052	0.87	0.87	0.87	0.87
NOACK Volatility, %	D5800	13	13	13	13
Color	D1500	2.5	2.5	2.5	2.5

*Typical test data may vary. Minor variations, which do not affect performance, may occur.*

## PACKAGING DETAIL & PART NUMBERS

PRODUCT PACK SIZE	UNIT WEIGHT	Cubic Feet	PALLET QTY	PALLET WEIGHT	PART NO.	PART NO.	PART NO.	PART NO.
Case 12/ 1L, net 12L	25.2	0.78	96	2450	B101Q	B106Q	B138Q	B109Q
Case 4/ 4L, net 16L	33.5	1.03	60	2050	B101L	B106L	B138L	B109L
Case 4/ 5L, net 20L	42.5	1.22	40	1750	B101G	B106G	B138G	B109G
Pail 18.9L (5 gl)	38.0	1.24	56	2170	B101P	B106P	B138P	B109P
Pail 20L	40.2	1.24	42	1735	B101J	B106J	B138J	B109J
Drum 208L (55 gl)	428	10.52	4	1760	B101D	B106D	B138D	B109D
Tote 1000L (265 gl)	1930	49.4	1	1930	B101T	B106T	B138T	B109T

## TYPICAL APPLICATIONS

- All SAE viscosities are formulated for use in gasoline fueled cars and light duty trucks
- Meets the performance requirements of API SP, SN PLUS, SN
- Formulated for use in most vehicles made in North America (Ford, GM, Chevy, Chrysler, Cadillac, Dodge, Jeep) and Asia (Honda, Toyota, Hyundai, Nissan, Mazda, Kia, Daewoo, Suzuki, Mitsubishi, Daihatsu)

*HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.*