

PRODUCT DESCRIPTION

BEX® Ultimate Performance Synthetic Oil and BEX® Advanced Performance Synthetic Blend Oil with DPF protection for High Mileage vehicle engines. Specially formulated with EX³ to provide extra engine protection in 3 key areas: viscosity stability, extended wear performance, and resistance to engine buildup. Utilizing advanced synthetic technology, BEX® oils exceed current industry performance requirements. Always consult the vehicle manual for proper fluid & maintenance guidelines. BEX® oils are warranted against defect when used & stored properly.

FEATURES & BENEFITS

- Lower ash content for compatibility in engines with diesel particulate filters (DPF)
- Ultimate protection against soot & sludge for peak engine performance
- Delivers viscosity stability & thermal endurance
- Helps maximize fuel economy & reduce emissions
- Fortified with enhanced additives to protect seals & reduce wear on higher mileage engines

TYPICAL PROPERTIES

TEST NAME	ASTM Method	5W-30 Full Synthetic	5W-30 Semi Synthetic
Kinematic Viscosity @ 100° C, cSt	D445	9.8	9.7
Kinematic Viscosity @ 40° C, cSt	D445	50.5	50.65
Viscosity Index	D2270	185	185
Flash Point °C / °F	D92	205 / 401	210 / 410
Pour Point °C / °F	D97	-50 / -58	-44 / -47
Sulfated Ash, Wt %	D874	< 0.8	< 0.8
TBN, mgKOH/g	D2896	7.5	7.5
Color	D1500	2.5	2.5

Typical test data may vary. Minor variations, which do not affect performance, may occur.

PACKAGING DETAIL & PART NUMBERS

PRODUCT PACK SIZE	UNIT WEIGHT	Cubic Feet	PALLET QTY	PALLET WEIGHT	PART NO.	PART NO.
Case 12/ 1L, net 12L	25.2	0.78	96	2515	B139Q	B691Q
Case 4/ 4L, net 16L	33.5	1.03	60	2055	B139L	B691L
Case 4/ 5L, net 20L	42.5	1.22	40	1780	B139G	B691G
Pail 18.9L (5 gl)	38.0	1.24	56	1640	B139P	B691P
Pail 20L	40.2	1.24	42	1735	B139J	B691J
Drum 208L (55 gl)	428	10.52	4	1760	B139D	B691D
Tote 1000L (265 gl)	1930	49.4	1	1930	B139T	B691T

TYPICAL APPLICATIONS

- For use in gasoline engines with over 75,000 miles on the odometer
- For use in vehicles requiring API SN and ILSAC GL-5 performance specifications

HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.