

PRODUCT DESCRIPTION

BEX® Ultimate Performance Synthetic Oils are specially formulated with EX³ to provide extra engine protection in 3 key areas: viscosity stability, extended wear performance, and resistance to engine buildup. Utilizing advanced synthetic technology, BEX® oils exceed current industry performance requirements. Always consult the vehicle manual for proper fluid & maintenance guidelines. BEX® oils are warranted against defect when used & stored properly.

FEATURES & BENEFITS

- 100% synthetic technology to extend drain intervals
- Ultimate protection against sludge & soot deposits for peak engine performance
- Friction modifiers & enhanced additives reduce engine wear & provide oxidation stability
- Formulated to protect high-compression gasoline direct injection engines
- Delivers low-speed pre-ignition mitigation
- Reduces sulfated ash for better emission system capability

TYPICAL PROPERTIES

TEST NAME	ASTM	5W-40	5W-50
Viscosity @ 100° C, cSt	D445	14.5	18.5
Viscosity @ 40° C, cSt	D445	86.8	115
Viscosity Index	D2270	178	180
Flash Point °C / °F	D92	215 / 419	215 / 419
Pour Point °C / °F	D97	-42 / -44	-42 / -44
CCS Apparent Viscosity, cP	D5293	5,400@-30C	5,800@-30C
MRV Apparent Viscosity cP	D4684	22,000@-35C	23,000@-35C
Color	D1500	Amber Liquid,	Transparent

Typical test data may vary. Minor variations, which do not affect performance, may occur.

PACKAGING DETAIL

PRODUCT PACK SIZE	UNIT WEIGHT	CUBIC FEET	PALLET QUANTITY	PALLET WEIGHT
Case 12/ 1L, net 12L	25.2	0.78	96	2450
Case 4/ 4L, net 16L	33.5	1.03	60	2050
Case 4/ 5L, net 20L	42.5	1.22	40	1750
Pail 18.9L (5 gal)	38.0	1.24	56	2170
Pail 20L	40.2	1.24	42	1735
Drum 208L (55 gal)	428	10.52	4	1760
Tote 1000L (265 gal)	1930	49.4	1	1930

TYPICAL APPLICATIONS

- All viscosities are formulated for use in modern gasoline engines
- Meets performance requirements of API SQ, SP, SN PLUS, SN
- Formulated for use in most vehicles made in North America (Ford, GM, Chevy, Chrysler, Cadillac, Dodge, Jeep) and Asia (Honda, Toyota, Hyundai, Nissan, Mazda, Kia, Daewoo, Suzuki, Mitsubishi, Daihatsu)

HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.