

PRODUCT DESCRIPTION

BEX® Two-Cycle Engine Oil is a premium, synthetic 2-stroke engine oil designed for use in water or air-cooled two-cycle engines. This product is formulated with synthetic base oils and premium performance additive package which contains anti-oxidants, defoamers, anti-wear compounds, dispersants, and friction modifiers. It provides enhanced engine cleanliness, prevents ring sticking, reduces spark plug fouling and eliminates engine smoking. Formulated for use in a wide array of applications including outboard engines, motorcycles, lawn mowers, scooters, golf carts, chain saws, and other two-stroke powered equipment. **SFU (suitable for use): NMMA TC-W3, API TC.** Always consult the equipment owner manual for proper fluid & maintenance guidelines. BEX® oils are warranted against defect when used & stored properly.

FEATURES & BENEFITS

- Provides superior fluidity/miscibility
- Helps prevent rust & corrosion and reduce engine wear & scuffing
- Prevents ring sticking and carbon build up on piston and other critical engine parts
- Helps reduce spark plug fouling & whiskering

TYPICAL PROPERTIES

TEST NAME	ASTM Method	Synthetic	Synthetic Blend
Viscosity @ 40°C cSt	D445	38.5	38
Viscosity @ 100°C cSt	D445	7.4	7.3
Viscosity Index	D2270	165	164
Sulfated Ash, Wt %	D874	< 0.1	< 0.1
Flash Point °C / °F	D92	150 / 302	150 / 302
Pour Point °C / °F	D97	-45 / -49	-45 / -49
TBN	D2896	5	5

Typical test data may vary. Minor variations, which do not affect performance, may occur.

PACKAGING DETAIL & PART NUMBERS

PRODUCT PACK SIZE	UNIT WEIGHT	Cubic Feet	PALLET QTY	PALLET WEIGHT	PART NO.	PART NO.	PART NO.
Case 12/1L, 12/QT	25.6	0.78	98	2515	B210Q	B212Q	B214Q
Case 4/4L, 4/1GL	33.5	1.03	60	1850	B210G	B212G	B214G
Pail 18L / 5GL	38.0	1.24	56	1636	B210P	B212P	B214P
Drum 208L (55 gl)	428	10.52	4	1760	B210D	B212D	B214D

FUEL MIXING RATIOS, OUNCES OF OIL TO GALLONS OF GASOLINE

GAS : VOL	1 GAL	2 GAL	3 GAL	4 GAL	5 GAL	6 GAL
GAS : OIL	Oz	Oz	Oz	Oz	Oz	Oz
16 : 1	8	16	24	32	40	48
20 : 1	6	13	19	26	32	38
24 : 1	5	11	16	21	27	32
25 : 1	5	10	15	20	26	31
40 : 1	3	6	10	13	16	19
50 : 1	3	5	8	11	13	16

HANDLING AND SAFETY INFORMATION - Refer to (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.